



PRODUCTS | PAVERS

# H<sub>2</sub>O PRO

**H<sub>2</sub>O PRO® Permeable Pavers** are an effective storm water management solution. Their 3<sup>1/8"</sup> (80 mm) thickness withstands heavy low speed vehicular loads, making them a suitable option for driveways, walkways, and parking lots.



H<sub>2</sub>O PRO Permeable Pavers in Timeless


DISCOVER  
more about this  
product



## Color (4x8)

Colors shown may vary from actual hues.

### SOLID




REFLECTION

## Dimensions

SOLD ON  
INDIVIDUAL PALLETES.

4 x 8 IN  
3<sup>1/8</sup> HEIGHT



## Colors (All Sizes)

Colors shown may vary from actual hues.

### BLENDED



TIMELESS




MAJESTIC


## Sizes and Dimensions

SOLD ON INDIVIDUAL PALLETES.


4 x 8 IN  
3<sup>1/8</sup> HEIGHT



8 x 8 IN  
3<sup>1/8</sup> HEIGHT



8 x 16 IN  
3<sup>1/8</sup> HEIGHT



H<sub>2</sub>O Pro Permeable Pavers in Timeless

## Permeable Interlocking Concrete Pavers

Permeable pavers are increasingly gaining the attention of media, builders, and property owners alike because of growing efforts to effectively manage storm water in municipalities and watershed districts across the country.



CONCRETE  
**MASONRY &  
HARDSCAPES**  
ASSOCIATION

Refer to the Interlocking Concrete Pavement Institute's Guide Specification for additional information on Permeable Interlocking Concrete Pavers.