


LED LANDSCAPE LIGHTING SOLUTIONS FOR RESIDENTIAL AND COMMERCIAL APPLICATIONS

ENHANCE YOUR OUTDOOR LIVING SPACE WITH LITE THE NITE LANDSCAPE LIGHTING SOLUTIONS!

Get ON with it!




We are very proud of the Lite the Nite brands. We stand by our mission to provide superior electrical components and service to benefit our clients, users, and associates.

Thank you for considering Lite the Nite!

- 6 Solar Power Supply
- 10 AC & DC Power Supplies
- 12 Uplights
- 14 Downlights
- 16 Pathlights
- **18** Hardscapes
- 20 Specialty
- 22 Accessories
- **24** LEDS
- 25 Certified Turtle Friendly





READY. SET. SOLAR

SOLAR POWER SUPPLY



Operating Temp:

4° to 140°F

Irrigation Association

SILVER | Landscape Lighting Category

Renewable Universal Power Supply

Our award-winning Solar Power Supply system relies on the **SUN** for its power, and features a 300W Battery to power anything low voltage.

INCLUDED:

Solar Panel

- 50W "shadow proof" solar panel Independently wired bypass diodes for enhanced chargability

Mounting Bracket

- LTN1-300RUPS: Expandable Heavy Duty Bracket Allows expansion to (2) 50W solar panels for faster recharge
- LTN2-300RUPS: Tenon Mount for 2 in. Round Pole Additional mounting options below

Stainless Steel Power Station

- 300W 14.2V 21.1 Ahr Rechargeable Battery (Replaceable)
- Solar Controller Driver
- Timer with Photo Eye
- U-Bolts (if necessary)



LTN-SL-SAL-BKT-ST-3-BK-G1 3" square tenon bracket



LTN-SL-SAL-BKT-RT-3-BK-G1 3" round tenon bracket



LTN-SL-SAL-BKT-WM-BK-G1
Wall mount bracket

(MORE BRACKET OPTIONS AVAILABLE UPON REQUEST)

SPECIFICATIONS:

Solar Power Supply with 300W Battery 2000 Charge Cycles or 5 years Operation Temp. Range -4°F to 140°F 3 Year System Warranty

TIMER OPERATION:

ON/OFF

Auto (full Dusk to Dawn) Dusk to 2/4/6/8 hours

OPERATION VOLTAGE:

Fully charged - 14.2 VDC Dropout - 11.8 VDC

LOAD CAPACTIY - HOURS OF OPERATION*


LOAD (WATTS)	28	35	47	71	143	285
HOURS	10	8	6	4	2	1

*Based upon fully charged battery at 285W. Hours of operation will vary if battery is not fully charged. Recommended NOT to use full charge capacity daily to ensure operation after cloudy or cold weather days.

PRODUCT #	COMPLETE SYSTEM		
LTN1-300RUPS	50W Solar Panel, Expandable Bracket, 300W Power Station & 10' Cable (U-Bolts if necessary)		
LTN2-300RUPS	50W Solar Panel, 2 in. Tenon Pole Mount, 300W Power Station & 10' Cable, 2 U-Bolts		
	ACCESSORIES		
LTN1-50WSP	50W Solar Panel		
LTN1-YCBL	Y-Shaped Extension Cable for Additional Panel		
LTN1-RUPSCBL-10	10ft Cable for Panel		
LTN1-RUPSUBOLT	U-Bolts		
LTN1-300WBAT	300W Rechargeable Battery		
LTN1-RUPSTMR	Power Station Timer		



Get ON with it!



Lite the Nite continues to stay ahead of the curve with the industries most advanced power sources for controlling any low voltage landscape lighting systems. We offer AC and DC output options to best suit your application.



POWER SUPPLIES

AC TRANSFORMERS



LTN1100AC

100W AC Transformer Suitable for smaller lighting projects Digital photo eye programming Manual ON/OFF Dusk to Dawn/Dusk to 1-9 hours

LTN3200AC/LTN3300AC

200W or 300W AC Transformer
12V-15V AC
Photocell/Timer/Astronomical clock/Manual
Overload LCD warning system
Circuit breaker protection
Quick connect taps
304 stainless steel housing

AC offers a simplistic and economic way to power your system.

DUAL TIMER CAPABILITY



Replaceable plug-in timer





DC POWER PACK



LTN2150

150W DC Power Pack (expandable up to 600W)

- Direct hardwire capability to any home control system!

RF remote control system

200W Surge Capable

Regulated variable flicker-free dimming EMI Free (Electromagentic Interference) Rechargeable capacitor

DC Wire Run Recommendations

	Total Wattage					
Wire Size	20	40	60	80	100	135
16	215	110	70	55	40	30
14	350	175	115	85	70	50
12	550	270	185	135	110	80
10	870	440	295	220	175	125

Maximum recommended wire length based on wire size and total wattage.

The wire selection table provides a maximum voltage drop of 20%.

(Calculated for the Nite Driver and Lite the Nite LED fixtures.)



LTN2150 Remote

The AC to DC conversion is eliminated, allowing LED's to run more efficiently, thus increasing lifespan.

600W)

DC is the preferred choice for all LEDs.


Built-in 0-10V
dedicated
terminal for home
control direct
connect!

UPLIGHTS



Installed using Ground
Stake (included) and
aimed upward for wall
wash and landscape
highlighting. Uplights
are the workhorse
that define shape and
details.

BU132BZ



UPLIGHTS

ALUMINUM



AU110TBZ (No LED) **AU115TBZ** (5W) **AU117TBZ** (7W)

Dimmable MR16 LED Optional

17°, 40°, & 60° spread



AU110TBL (No LED) **AU115TBL** (5W) **AU117TBL** (7W)

Dimmable MR16 LED Optional 17°, 40°, & 60° spread



ACU210ABZ (No LED) **ACU215ABZ** (5W) **ACU217ABZ** (7W)

Dimmable MR16 LED Optional 17°, 40°, & 60° spread



AC110ABZ (No LED) **AC115ABZ** (5W) **AC117ABZ** (7W)

Dimmable MR16 LED Optional 17°, 40°, & 60° spread - 12V

BRASS



BU132BZ (2.5W) MR8 LED Included 175 Lumen - 3000K 80° spread



BU110BZ (No LED) **BU115BZ** (5W) **BU117BZ** (7W)

Dimmable MR16 LED Optional 17° , 40° , and 60° beam spread



BUR106BZ

6W - LED Included 316 lumens 3000K Linear, Clear, & Frosted Lens

BUR101BZ 11W - LED Included 819 lumens 3000K Linear, Clear, & Frosted Lens



BU1412BZ

12W - Par36 Lamp Included 680 lumens 3000K 25°, 45°, or 60° beam spread Louvred Lens

DOWNLIGHTS



Surface mounted downlights (mounting brackets available) are designed for subtle wall wash creating unique accents and drama. May also be wall mounted where up lighting is needed.



DOWNLIGHTS

ALUMINUM



Dimmable MR16 LED Optional 17°, 40°, & 60° spread



Optional


ACD210ABZ (No LED) ACD215ABZ (5W) ACD217ABZ (7W) Dimmable MR16 LED Optional

Dimmable MR16 LED Optiona 17°, 40°, & 60° spread











ACD210BK (No LED) **ACD215BK**(5W) **ACD217BK**(7W)

Dimmable MR16 LED Optional 17°, 40°, & 60° spread





BRASS

BD132BZ (2.5W)

MR8 LED Included 175 Lumen - 3000K 80° spread Base Included



BD110BZ (No LED) **BD115BZ** (5W) **BD117BZ** (7W)

White

Dimmable MR16 LED Optional 17°, 40°, & 60° spread Base Included





PATHLIGHTS



PATHLIGHTS

ALUMINUM

Dimmable 4W LED and ground stake included Integrated LED module 169 lumens - WW - 2800k Level light output to 20% system voltage drop 36" SPT-2W 18AWG copper lead wire



AP136TBZ (22" ht)

6" cone shade

AP148TBZ (22" ht) AP136TBZ-2 (18" ht) AP148TBZ-2 (18" ht) AP118TBZ-2 (18" ht)

8" tier shade

AP118TBZ (22" ht)

AX1PHTBZ

Frosted Lens

8" dome shade

BRASS

Dimmable 4W LED and ground stake included Integrated LED module 357 lumens - WW - 3000k 36" SPT-2W 18AWG copper lead wire Includes clear and frosted lens



n = Certified Turtle Friendly



BP116BZ (22" ht)

6" dome shade



BP126BZ (22" ht)

6" cone shade



BP166BZ (22" ht) BP116BZ-2 (18" ht) BP126BZ-2 (18" ht) BP166BZ-2 (18" ht)

6" pyramid shade



12" or 18" Stem Lengths Available



4W LED Light Array



BP118BZ (22" ht)

8" dome shade



BP128BZ (22" ht) BP118BZ-2 (18" ht) BP128BZ-2 (18" ht) BP156BZ-2 (18" ht)

8" cone shade



BP156BZ (22" ht)

8" deep shade

BLACK

Dimmable 2W LED optional Ground stake included 20" height 36" SPT-2W 18AWG copper lead wire Frosted Lens



L1522D - 2W G4 BI-PIN Plug-In

3000K WW 8/18V AC / 10/30V DC

BP1505BK (NO LED) BP1525BK (with LED)

5" flat top hat

HARDSCAPES





Lite the Nite's hardscape collection is an ingenious lighting option for projects involving decking, stairs, railings, walls, etc. built using just about any material - from wood, to brick, to stone. The slim profile allows for total concealment, yet provides a spray of light to brighten hardscapes.



HARDSCAPES

UNDERCAP

AH1023BZ (2W - Aluminum) BH1033BZ (3W - Brass)

Available in 4" (2W - 3000K): AH1023ABZ-4 (Aluminum) BH1023BZ-4 (Brass)



Replaceable LED module

Under Cap and Linear mounting brackets included 3000K - Dimmable Damp location listed 5 ft. SPT-1W 18AWG copper lead wire





REPLACEMENT LED

LAH1023BZ (2W - Aluminum) **LBH1033BZ** (3W - Brass)

Replace LED without removing fixture!





DECK



BDL190BZ (No LED) **BDL192BZ** (2W)

2W 3000K Bi-Pin Disk LED Optional (L2923D)

LINEAR



BLH105BZ (5W)

Mounting screws included Integrated LED - Dimmable - 3000K 6ft. 18AWG copper lead wire



STEP LIGHTS

Vertical surface mount - Dimmable Integrated LED module - 3000K NO BACK BOX REQUIRED





BST105BZ (5W)

3" x 5" x 7/8" 51 Lumens



ADA Compliant ADA



Retrofit Driver Available (8W/12W)

- Line voltage conversion to low voltage



BST106BZ (6W)

2" x 9" x 7/8" 53 Lumens





Custom Back Plate Option

Sized to your needs!





BST109BZ (9W)

3" x 9" x 7/8" 90 Lumens







SPECIALTY



WELL LIGHT



BW110BZ (No LED) **BW115BZ** (5W) **BW117BZ** (7W) MR16 Available with 17°, 40°, or 60°

SUBMERSIBLE



BSU110NB
Great for backyard ponds & under waterfalls
MR16
Natural Brass
30ft Insulated Lead Wire

UP/DOWN SCONCE



BUDS110BZ
(2) MR16 Dimmable LED Lamp
Ordered Seperately

LINE VOLTAGE



SPECIALTY

POOL CAGE LIGHT

BPC105RGB/WW-BZ BPC105RGB/WW-WH

5W - BRASS

Dimmable, Integrated color-changing RGB & WW LEDs

10 ft Cord

Waterproof Connectors

Remote Included



TIKI TORCH

BPT177BZ

Replaceable LED module Stabilizer ground stake and brass cap included 6 FT (70.5 in.) - TOTAL HEIGHT

TIKI TORCH FUEL



X1TIKI-PLN (Plain) Light A
X1TIKI-CIT (Citronella)
X1TIKI-LMEU (Lemon Eucalyptus)





ACCESSORIES

WIRE & CONNECTORS



	Model	Description		
	CONNECTORS			
X1WPC Waterproof Connector 20-pc pack		Waterproof Connector 20-pc pack		
	X1WPC-200	C-200 Waterproof Connector 200-pc pack		
	X1WPCM	MEDIUM Waterproof Connector 20-pc pack		
	X1WPCM-200	MEDIUM Waterproof Connector 200-pc pack		



WIRE

Model	Description		
WIRE			
X1LVW122	Low Voltage Wire 12/2		
X1LVW122-50	Low Voltage Wire 12/2 50'		
X1LVW142	Low Voltage Wire 14/2 500'		
X1LVW142-50	Low Voltage Wire 14/2 50'		

MOUNTING BASES

GUTTER MOUNT



Model	Description
BASES	
SX1GMDB	Stainless Steel Gutter Mount



TREELIGHT MOUNT

Model	Description
BASES	
X1TM7BZ	7" TreeLight Mount
X1TM4BZ	4" TreeLight Mount

AX1ABSE-BZ AX1ABSE-WH AX1ABSE-BK







Model	Description		
BASES			
AX1ABSE-BZ	Bronze Aluminum Architectural Base		
AX1ABSE-WH	White Aluminum Architectural Base		
AX1ABSE-BK	Black Aluminum Architectural Base		







ACCESSORIES



RISERS & STEMS

6" - 12" - 18"

Available in Aluminum or Brass

Model	Description		
RISERS			
AX1RSR6TBZ	6" Aluminum Fixture Riser		
AX1RSR2TBZ	12" Aluminum Fixture Riser		
AX1RSR8TBZ	18" Aluminum Fixture Riser		
AX1STM2TBZ	12" Aluminum Fixture Stem		
AX1STM8TBZ	18" Aluminum Fixture Stem		
BX1RSR6BZ	6" Brass Fixture Riser		
BX1RSR2BZ	12" Brass Fixture Riser		
BX1RSR8BZ	18" Brass Fixture Riser		
BX1STM2BZ	12" Brass Fixture Stem		
BX1STM8BZ	18" Brass Fixture Stem		

STAKES





Model	Model Description		
STAKES			
X1STK8	8" Plastic Fixture Stake		
X1STKL8	8" Oversized Plastic Fixture Stake		
BX1STK8	8" Brass Fixture Stake		
X1HDSSTK	Heavy Duty PVC Stabilizer Stake		
X1HDSSTK-BCAP	Optional Brass Cap for X1HDSSTK		
X1HDSSTK-ACAP	Replacement Aluminum Cap for X1HDSSTK		



LEDS



5W/7W - MR16

Dimmable

LED Color Replacement Bulbs RED BLUE GREEN







Add a splash of color for special holidays. The 5-watt MR16 LED is replaceable Create a festive highlight with red, green and blue bulbs (non-dimmable).

Model	Wattage	Color Temp	Beam Spread
MR16			
L21521D	5W	2700K	17°
L21524D	5W	2700K	40°
L21526D	5W	2700K	60°
L21531D	5W	3000K	17°
L21534D	5W	3000K	40°
L21536D	5W	3000K	60°
L21541D	5W	4000K	17°
L21544D	5W	4000K	40°
L21546D	5W	4000K	60°
L21551D	5W	5000K	17°
L21554D	5W	5000K	40°
L21556D	5W	5000K	60°
L21731D	7W	3000K	17°
L21734D	7W	3000K	40°
L21736D	7W	3000K	60°
MR16 Color			
L115B4	5W	BLUE	40°
L115G4	5W	GREEN	40°
L115R4	5W	RED	40°











L2923D - 2W L192BD - BLUE 3000K or **BLUE** LED Dimmable LED G4 BI-PIN BLUE



2.5W - MR8

Model	Wattage Color Temp Be		Beam Spread
MR8			
L13238	2.5W	3000K	80°



12W - Par36

Dimmable

Model	Wattage	Color Temp	Beam Spread
PAR36			
L14123D-25	12W	3000K	25°
L14123D-45	12W	3000K	45°
L14123D-60	12W	3000K	60°



Dimmable

Model	Wattage	Color Temp		
Pathlight LED Array				
BX1PHABZ	4W	3000K		
AX1PHTBZ	4W	2800K		





L1522D - 2W 2700K Replaceable LED for BP1505BK (see pg. 17)



CERTIFIED TURTLE-FRIENDLY





Lite the Nite offers a full line of certified turtle-friendly landscape lighting fixtures and replacement lamps. The *Florida Fish and Wildlife Conservation Commission* has established guidelines for the use of lighting on and around important sea turtle nesting beaches. You can help *protect* these turtles, and their hatchlings, from lighting-induced disorientation by installing Lite the Nite's turtle-friendly lighting designed specifically in support of sea turtles and other beach dwelling wildlife.

Pathlights


CERTIFICATION #2019-205



Step Lights

CERTIFICATION #2018-027

Brass fixture, choice of 5" x 3" (5W) or 9" x 3" (8W) 12V AC Dimmable LED



Brass fixtures, choice of 8" dome, cone, or deep cone style hat, choice of 12" or 18" stem, 12V AC Dimmable LED



Custom Back Plate OptionSized to your needs!



BST108BZ-A



BDL192BZ-A

Deck Light

Brass fixture, 2W Dimmable LED





L192A LED Disk 2W G4 Bi-Pin CERTIFICATION #2019-206



L115A4 LED 5W MR16 CERTIFICATION #2019-207



BX1PHABZ-A LED 4W Light Array CERTIFICATION #2019-205





CONNECT WITH US ON OUR WEBSITE!



FOLLOW US ON SOCIAL MEDIA TO STAY UP TO DATE WITH LITE THE NITE!








@ltnlandscapelighting



Lite the Nite

MARKETING MATERIALS AND DISPLAYS AVAILABLE UPON REQUEST





BUSINESS CARD HERE

650 E Algonquin Rd, Suite 405 Schaumburg, IL. 60173

> info@litethenite.com +1 847.496.5276

