

NCIF Group

#127 North Fuzhou Road,
Qingdao 266000, China



Fiberback Woven Landscape Fabric FB50

PROPERTY	TEST METHOD	UNIT	VALUE
Weight	ASTM D 5261	oz/yd ²	5
Grab Tensile	ASTM D 4632	lbs	125x70
Grab Elongation	ASTM D 4632	%	12
Trapezoid Tear Strength	ASTM D 4533	lbs	50x30
CBR Puncture Resistance	ASTM D 6241	lbs	325
Permittivity	ASTM D 4491	sec-1	0.1
Water Flow	ASTM D 4491	gpm/ft ²	10
AOS	ASTM D 4751	US Sieve	40
UV Resistance at 500hrs	ASTM D 4355	%	70

Rev. May 2025

Disclaimer: NCIF warrants that at the time of delivery the product furnished hereunder shall conform to the specification stated herein. NCIF assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. NCIF disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.