



Application Guide for ProGanics® DUAL™ Biotic Soil + Erosion Control

ProGanics® DUAL™ is mixed at a rate of 75 pounds per 100 gallons of water

Application / Loading Procedures

- A.** Strictly comply with equipment Manufacturer's installation instructions and recommendations. Use approved hydro-spraying machines with the appropriate nozzle whenever possible to achieve best soil coverage. Apply from opposing directions to assure uniform soil surface coverage.
- B.** To ensure proper application rates, measure and stake area.
- C.** Fill 1/3 of mechanically agitated hydroseeder with water. Turn pump on for 30-60 seconds to purge and pre-wet lines. Turn pump off.
- D.** Turn agitator on, open recirculation valve and load low density materials first (i.e. seed and Prescriptive Solutions).¹
- E.** Continue slowly filling tank with water while loading ProGanics® DUAL™ at a rate of 75 pounds per 100 gallons of water.
- F.** Consult loading chart on the back page to determine the number of bags to be added for desired area and application rate.
- G.** ProGanics DUAL should be completely loaded before water level reaches 75% of the top of tank.
- H.** Add fertilizer and other high density materials as water level approaches the top of the tank.
- I.** Top off with water and mix until ProGanics DUAL is fully broken apart and hydrated (minimum of 10 minutes — increase mixing time when applying in cold conditions). It is very important to fully hydrate ProGanics DUAL and activate the bonding additives to obtain proper viscosity and optimal performance.
- J.** Shut off recirculation valve to minimize potential for air entrainment within the slurry.
- K.** Slow down agitator(s) to minimum speed and start applying with an appropriate nozzle.
- L.** Spray in opposing directions for maximum soil coverage.
- M.** Upon completion of application, return to water source to repeat mixing and application sequence or to flush equipment. Thoroughly purge pump and all lines of residual materials from previous load. Monitor residual material in tank after purging; excess material may reduce number of bales to be mixed in subsequent loads.

Apply ProGanics DUAL as directed above being sure to include all Prescriptive Solutions, fertilizer and seed at their recommended rates.

¹ Do not add additional tackifiers or polymers to this pre-mixed formulation without first consulting Profile Products.

Application Guide for ProGanics® DUAL™ Biotic Soil + Erosion Control

Loading Chart for ProGanics DUAL

Working Capacity Size (gal)	# of 50-lb bales	lb	Displacement (gal)	4,000 lb/ac		5,500 lb/ac		6,500 lb/ac	
				Sq ft	Acres	Sq ft	Acres	Sq ft	Acres
250	3.75	188	280	2,042	0.047	1,485	0.034	1,257	0.029
500	7.5	375	560	4,084	0.094	2,970	0.068	2,513	0.058
750	11.25	563	840	6,126	0.141	4,455	0.102	3,770	0.087
1,000	15	750	1,120	8,168	0.188	5,940	0.136	5,026	0.115
1,500	22.5	1,125	1,680	12,251	0.281	8,910	0.205	7,539	0.173
2,000	30	1,500	2,240	16,335	0.375	11,880	0.273	10,052	0.231
2,500	37.5	1,875	2,800	20,419	0.469	14,850	0.341	12,565	0.288
3,000	45	2,250	3,360	24,503	0.563	17,820	0.409	15,079	0.346
3,500	52.5	2,625	3,920	28,586	0.656	20,790	0.477	17,592	0.404
4,000	60	3,000	4,480	32,670	0.750	23,760	0.545	20,105	0.462
5,000	75	3,750	5,600	40,838	0.938	29,700	0.682	25,131	0.577

Application Rates

% Organic Matter ¹	Slope Gradient	English (lb/ac)	Metric (kg/ha)
< 5.0 and ≥ 1.5	≤ 4H:1V	4,000	4,480
< 1.5 and ≥ 0.75	> 4H:1V and ≤ 3H:1V	5,500	6,160
< 0.75	> 3H:1V and ≤ 2H:1V	6,500	7,290

For conversions:

1 lb = 0.454 kg

1 ac = 0.41 ha

lb/ac x 1.12 = kg/ha

1 kg = 2.20 lb

1 ha = 2.47 ac

¹ Based on Soil Test Results. Refer to Profile's Soil Testing and Interpretation Guide for more information.



Solutions for your Environment™

PROFILE Products LLC

750 W. Lake Cook Road • Suite 440 • Buffalo Grove, IL 60089

800-508-8681 • +1-847-215-1144 • profileproducts.com

Profile and ProGanics are registered trademarks of PROFILE Products LLC. Biotic Soil Media, BSM, DUAL and Solutions for your Environment are trademarks of PROFILE Products LLC.

U.S. Patents #'s: 7,854,926; 8,728,460; 10,266,457 • Canada Patent #: 2,616,578



Find us on 
facebook.com/profileEVS





Bowman
Construction
Supply Inc.



Quick
Supply Co.



Cascade
GEOSYNTHETICS

LOCATIONS & CONTACT INFO

ASP ENTERPRISES

aspent.com
salesasp@aspent.com

BOWMAN CONSTRUCTION SUPPLY

bowmanconstructionsupply.com
salesbcs@bowmanconstructionsupply.com

QUICK SUPPLY CO.

quicksupplyco.com
salesquick@quicksupplyco.com

CASCADE GEOSYNTHETICS

cascadegeos.com
salescascade@cascadegeos.com

St. Louis, MO 636.343.4357
Omaha, NE 402.861.8579
Kansas City, MO 816.554.1191
Wichita, KS 316.393.1554

Denver, CO 303.696.8960
Colorado Springs, CO 719.257.7840
Loveland, CO 970.535.0863

Des Moines, IA
515.289.1271

Portland, OR
971.339.1020

SOLUTIONS WE SUPPLY

GEOSYNTHETICS

Filter Fabrics

Stabilization Fabrics

Geogrids

- Road Grids
- Wall Grids
- Slope Stabilization

Specialty Fabrics

Composite Geomembranes

- GCLs, PVC, HDPE, LLDPE, EPDM, Granular Bentonite

SEDIMENT CONTROL

Inlet Protection

- Grated Inlet, Curb Inlet, Area Inlet Protection

Ditch Checks

- Triangle Silt Dike
- GeoRidge

Perimeter Protection

- High and Low-Porosity Silt Fence, Straw Wattles, Silt Socks
- Safety Fence

Flocculants & Water Treatment

- Polymer-Based & Natural Flocculants

Sediment Basin Skimmers

Dewatering Bags

Trackout Control

- FODS
- Rumble Grates

Turbidity Curtains

EROSION CONTROL

Basic Hydraulically Applied Mulches

- Wood
- Paper
- Blends
- Straw

High-Performance Hydraulically

Applied Products

- BFM
- FGM
- Additives & Tackifiers

Temporary Erosion Control Blankets

- Coir & Jute Mat/Nettings
- Short-Term ECBs
- Extended-Term ECBs

Permanent Erosion Control Blankets

- Turf Reinforcement Mats
- HP-TRMs
- Anchor Reinforced Vegetation System

Structural BMPs

- Transition Mats
- Geoweb Cellular Confinement
- Composite Vegetated Armor System
- Flex MSE Vegetated Wall System
- Articulated Concrete Block
- Gabions
- Grout-Filled Geotextile Mats

Vegetation Establishment

- Native Seed & Turf Seed
- Fertilizers
- Organic Soil Additives
- Stratavault Soil Cells

STORMWATER MANAGEMENT

Water Quality

- Inlet Filter Boxes
- Pre-Treatment Chamber
- Nutrient Separating Baffle Boxes
- High-Flow Biofiltration Media
- Hydrodynamic Separators
- Stratavault

Water Quantity

- Modular Underground Storage Systems
- Chamber Detention Systems

Drainage

- HDPE Swale Liner
- Pipe & Fittings
- Drainage Composites
- Strip Drain

Inlet Structures

- PVC
- Drain Basins, In-Line Drains
- Landscape

Permeable Pavers

- Permeable Articulating Concrete Block
- Grass Pavers
- Gravel Pavers
- Concrete Pavers

SPECIALTY

Natural & Synthetic Coir Fiber Logs

Vegetated Reinforced Soil Slopes

Soil Anchors

Root Barrier System

AquaBlok

Muscle Wall

We are full line distributors of construction materials for all project types. Contact us for assistance with a project. From specification and development to installation and completion, we're here to help with all of your site solution needs.

GEOSYNTHETICS | EROSION CONTROL | STORMWATER MANAGEMENT
SEDIMENT CONTROL | REVEGETATION & SOIL AMENDMENTS