SECTION 32 01 90.16 Amending Soils BioPrime™ Sustained-Release Biostimulant

GENERAL

1.01 SUMMARY

- A. This section specifies the hydraulically-applied BioPrime™ Sustained-Release Biostimulant designed to enhance long-term plant vitality. With a guaranteed nutritive analysis of 18-0-0 (N-P-K), its four active ingredients include slow-release Nitrogen, seaweed extract, humic acid, and endo mycorrhizae. The Nitrogen's proprietary sustained-release technology is ideally suited for revegetation of disturbed or denuded sites. Depending on site precipitation amounts and biological soil activity, the Nitrogen is released for up to 17 months.
- B. Related Sections: Other Specification Sections, which directly relate to the work of this Section include, but are not limited to the following:
 - 1. Section 01 57 00 Temporary Erosion and Sediment Control
 - 2. Section 02 24 23 Chemical Sampling and Analysis of Soils
 - 3. Section 31 00 00 Earthwork
 - 4. Section 31 25 00 Erosion and Sedimentation Controls
 - 5. Section 31 91 00 Planting Preparation
 - 6. Section 32 92 00 Turf and Grasses

1.02 SUBMITTALS

- A. Product Data: Submit manufacturer's product data and installation instructions. Include required substrate preparation, list of materials and application rate.
- B. Certifications: Manufacturer shall submit a letter of certification that the product meets or exceeds all technical and packaging requirements and is made in the USA.

1.03 DELIVERY, STORAGE AND HANDLING

A. Deliver materials and products in weather-resistant factory labeled packages. Store and handle in strict compliance with manufacturer's instructions and recommendations. Protect from damage, weather, excessive temperatures and construction operations.

PRODUCTS

2.01 ACCEPTABLE MANUFACTURER

A. PROFILE Products LLC
750 Lake Cook Road – Suite 440
Buffalo Grove, IL 60089
International - +1-847-215-1144
United States and Canada – 800-366-1180 (Fax 847-215-0577)
www.profileproducts.com

2.02 MATERIALS

A. The Sustained-Release Biostimulant shall be BioPrime and conform to the following typical property values:

| Performance Properties | Test Method | Unit | Tested Value | |
|---------------------------------|-------------|------|--------------|--|
| Vegetation Establishment | ASTM D7322 | % | ≥ 400 | |
| Environmental Properties | Test Method | Unit | Tested Value | |
| Ecotoxicity | EPA 2021.0 | n/a | Non-Toxic | |

2.03 COMPOSITION

- A. All components of the Sustained-Release Biostimulant shall be a micronized powder, pre-packaged by the manufacturer to assure both material performance, optimal mixing and compliance with the following values. No chemical additives with the exception of hydraulic mulch, fertilizer, soil neutralizers, biotic soil media, and additional biostimulant materials should be added to this product.
 - 1. Guaranteed Analysis 18-0-0
 - a) Total Nitrogen 18%
 - I. 1% Urea Nitrogen
 - II. 10.5% Water Insoluble Nitrogen
 - II. 6.5% Other Water Insoluble Nitrogen*
 - * 6.5% controlled release Nitrogen from methylenediurea and dimethylenetriurea
 - b) 1% Seaweed Extract
 - c) 1% Humic Acid
 - d) 1% Endo mycorrhizae fungi:
 - I. Glomus intradices
 - II. Glomus aggregatum
 - III. Glomus mosseae
 - e) 79% Inorganic Mineral (clay)

2.04 PACKAGING

A. Bags: Net Weight – 40 lb (18.1 kg), weather-resistant Pallets: Weather-proof, stretch-wrapped with pallet cover Pallet Quantity: 50 bags/pallet or 1 ton (909 kg)/pallet

EXECUTION

3.01 SOIL TESTING

- A. Soil Samples shall be taken and sent to a third-party, independent lab for analysis and in compliance with Section 02 24 23 Chemical Sampling and Analysis of Soils, if applicable.
- B. The tests shall include analysis and interpretation of results.
- C. The soil testing methods used shall be compliant with recognized agronomic testing standards, as outlined in *Section 02 24 23* The soil testing methods used shall be compliant with recognized agronomic testing standards, as outlined in *Section 02 24 23 Chemical Sampling and Analysis of Soils*, for revegetation of disturbed sites.
- D. Soil Analysis shall include results for:

- 1. Soil pH
- Soluble Salts
 Excess Carbonate
- 4. Organic Matter
- 5. Nutrient readings for:
 - i. Nitrogen, Phosphorus, Potassium
 - ii. Magnesium, Calcium, Sodium, Manganese, Sulfur, Zinc, Copper, Iron, Boron
- 6. Cation Exchange Capacity
- 7. Percent Base Saturation Sodium
- E. ProGanics™ BSM™, JumpStart™, Aqua-pHix™ and NeutraLime™ Dry or other amendments shall be specified according to Section 32 01 90.16 - Amending Soils and applied with the hydroseeding slurry at Manufacturer recommended rates based on soil test results.

3.02 VEGETATION SPECIES SELECTION

- A. Once soils have been analyzed for agronomic potential and amendment recommendations, selection of suitable plant species for achieving sustainable growth and effective erosion control shall be determined by a qualified seed supplier, consulting professional and/or regulatory agency. Species selection and establishment shall be compliant with Section 32 92 00 - Turf and Grasses, if applicable.
- B. Site and project specific information considered for species selection shall include:
 - 1. Project Location and Planning
 - i. Climate
 - ii. Elevation
 - iii. Aspect

 - iv. Slope/Gradientv. Permanent or Temporary Planting
 - vi. Installation Date(s)
 - 2. Soil Conditions
 - i. Soil Texture
 - ii. Soil pH
 - iii. Toxicities/Deficiencies noted in the previous section.
 - 3. Site Maintenance Requirements
 - i. Mowing
 - ii. Irrigation
 - iii. Animal grazing preference
 - 4. Preferred Vegetation
 - i. Drought Tolerant
 - ii. Native Vegetation
 - iii. Shrub Species
 - iv. Turf Grasses
 - v. Cool Season
 - vi. Warm Season
 - vii. Blend of Cool and Warm Season
 - viii. Legume Species
 - ix. Cover Crops

- A. Use Profile Soil Solutions Software (PS³) or other reputable software program to facilitate design and selection of erosion control techniques.
- B. Separate analysis shall be conducted for slope and channel erosion protection criteria, if necessary.
- C. Selection of erosion and sediment control techniques shall be detailed and in compliance with *Section* 31 25 00 *Erosion and Sedimentation Controls*, if applicable

3.04 SUBSTRATE PREPARATION

- A. Examine substrates and conditions where materials will be applied. Apply product to geotechnically stable slopes that have been designed and constructed to divert runoff away from the face of the slope. Do not proceed with installation until satisfactory conditions are established.
- B. Depending upon project sequencing and intended application, prepare seedbed in compliance with other specifications under Section 1.01 B

3.05 INSTALLATION

Strictly comply with manufacturer's installation instructions and recommendations. Use approved hydroseeding machines to apply Sustained-Release Biostimulant. No chemical additives with the exception of hydraulic mulch, fertilizer, soil neutralizers, biotic soil media, and additional biostimulant materials should be added to this product. Install materials at the application rates based on the main limiting factor provided by the soil test data in the following chart:

| Soil Characteristics | | | | | | Product Application Rates | |
|----------------------|------------------|------------------|---------------|----------------|---------------|---------------------------|-----------|
| EC ¹ | TDS ² | SAR ³ | CEC⁴ | Organic Matter | Organic Acids | BioPrime™ | BioPrime™ |
| mmhos/cm | ppm | n/a | % Sodium | % | % | lb/ac | kg/ha |
| < 0.4 | < 256 | < 2.0 | < 2.5 | ≥ 5 | ≥ 5 | Ideal Range | |
| ≥ 0.4 & < 0.75 | ≥ 256 & < 480 | ≥ 2.0 & < 3.0 | ≥ 2.5 & < 4.0 | ≥ 2.0 & < 5.0 | ≥ 2.5 & < 5.0 | 40 | 45 |
| ≥ 0.75 & < 1.5 | ≥ 480 & < 960 | ≥ 3.0 & < 4.0 | ≥ 4.0 & < 6.0 | ≥ 1.5 & < 2.0 | ≥ 1.7 & < 2.5 | 80 | 90 |
| ≥ 1.5 & < 3.0 | ≥ 961 & < 1,920 | ≥ 4.0 & < 5.0 | ≥ 6.0 & < 7.0 | ≥ 0.75 & < 1.5 | ≥ 1.0 & < 1.7 | 120 | 134 |
| ≥ 3.0 & < 7.0 | ≥ 1920 & < 4,480 | ≥ 5.0 & < 7.0 | ≥ 7.0 & < 15 | < 0.75 | < 1.0 | 160 | 179 |
| ≥ 7.0 | ≥ 4,480 | ≥ 7.0 | ≥ 15 | N/A | N/A | Contact Manufacturer | |

^{1.} Electrical Conductivity 2. Total Dissolved Solids 3. Sodium Adsorption Ratio 4. Cation Exchange Capacity – Percent Sodium

3.06 CLEANING AND PROTECTION

- A. After application, thoroughly flush the tank, pumps and hoses to remove all material. Wash all material from the exterior of the machine and remove any slurry spills. Once dry, material will be more difficult to remove.
- B. Clean spills promptly. Advise owner of methods for protection of treated areas. Do not allow treated areas to be trafficked or subjected to grazing.

3.07 INSPECTION AND MAINTENANCE

- A. All inspections and maintenance recommendations shall be conducted by qualified professionals consistent with the owner, engineer/specifier and regulatory entity(s) expectations.
- B. Initial inspections shall insure installations are in accordance with the project plans and specifications with material quantities and activities fully documented. Refer to Section 32 92 00 Turf and Grasses for any additional details.

- C. Subsequent inspections shall be conducted at pre-determined time intervals and corrective maintenance activities directed after each significant precipitation or other potentially damaging weather or site event.
- © 2016 PROFILE Products LLC. All Rights Reserved. A copyright license to reproduce this specification is hereby granted to non-manufacturing landscape architects, specification writers and designers. Reproduction or modification of this specification by manufacturers or their representatives is expressly forbidden.

 Revision Date: 12/2016









LOCATIONS & CONTACT INFO

ASP ENTERPRISES

aspent.com

salesasp@aspent.com

St. Louis, MO Omaha, NE 636.343.4357 402.861.8579

Kansas Citv. MO 816.554.1191

Wichita, KS 316.393.1554

BOWMAN CONSTRUCTION SUPPLY bowmanconstructionsupply.com

salesbcs@bowmanconstructionsupply.com salesquick@quicksupplyco.com

Denver, CO Colorado Springs, CO

303.696.8960 Loveland, CO 970.535.0863

OUICK SUPPLY CO.

quicksupplyco.com

Des Moines, IA 515.289.1271

CASCADE GEOSYNTHETICS

cascadegeos.com

salescascade@cascadegeos.com

Portland, OR 971.339.1020

SOLUTIONS WE SUPPLY

GEOSYNTHETICS

Filter Fabrics

Stabilization Fabrics

Geogrids

- Road Grids
- Wall Grids
- Slope Stabilization

Specialty Fabrics

Composite Geomembranes

• GCLs, PVC, HDPE, LLDPE, EPDM, Granular Bentonite

SEDIMENT CONTROL

Inlet Protection

· Grated Inlet, Curb Inlet, Area Inlet Protection

Ditch Checks

- · Triangle Silt Dike
- GeoRidge

Perimeter Protection

- · High and Low-Porosity Silt Fence, Straw Wattles, Silt Socks
- Safety Fence

Flocculants & Water Treatment

Polymer-Based & Natural Flocculants

Sediment Basin Skimmers

Dewatering Bags

Trackout Control

- FODS
- Rumble Grates

Turbidity Curtains

EROSION CONTROL

719.257.7840

Basic Hydraulically Applied Mulches

- Wood
- Paper
- Blends
- Straw

High-Performance Hydraulically Applied Products

- FGM
- · Additives & Tackifiers

Temporary Erosion Control Blankets

- Coir & Jute Mat/Nettings
- Short-Term ECBs
- Extended-Term ECBs

Permanent Erosion Control Blankets

- Turf Reinforcement Mats
- HP-TRMs
- Anchor Reinforced Vegetation System

Structural BMPs

- Transition Mats
- Geoweb Cellular Confinement
- Composite Vegetated Armor System
- Flex MSE Vegetated Wall System
- Articulated Concrete Block
- Gabions
- · Grout-Filled Geotextile Mats

Vegetation Establishment

- · Native Seed & Turf Seed
- Fertilizers
- · Organic Soil Additives
- Stratavault Soil Cells

STORMWATER MANAGEMENT

Water Quality

- Inlet Filter Boxes
- Pre-Treatment Chamber
- Nutrient Separating Baffle Boxes
- · High-Flow Biofiltration Media
- · Hydrodynamic Separators
- Stratavault

Water Ouantity

- · Modular Underground Storage Systems
- Chamber Detention Systems

Drainage

- HDPE Swale Liner
- Pipe & Fittings
- · Drainage Composites
- Strip Drain

Inlet Structures

- PVC
- · Drain Basins, In-Line Drains
- Landscape

Permeable Pavers

- Permeable Articulating Concrete Block
- Grass Pavers
- · Gravel Pavers
- Concrete Pavers

SPECIALTY

Natural & Synthetic Coir Fiber Logs **Vegetated Reinforced Soil Slopes** Soil Anchors **Root Barrier System** AquaBlok Muscle Wall

We are full line distributors of construction materials for all project types. Contact us for assistance with a project. From specification and development to installation and completion, we're here to help with all of your site solution needs.