



# Profile® Wood with Tack Hydraulic Mulch



**GREEN DESIGN  
ENGINEERING™**  
EARTH-FRIENDLY SOLUTIONS  
FOR SUSTAINABLE RESULTS™

Solutions for your Environment™

## Description

Profile® Wood with Tack is a biodegradable, Hydraulic Mulch (HM) composed of 100% recycled Thermally Refined™ virgin wood fibers and wetting agents (including high-viscosity colloidal polysaccharides). The HM is made in the US, plastic-free, and phytosanitized to eliminate potential weed seeds and pathogens. Upon application, the product forms an intimate bond with the soil surface to create a porous, absorbent and flexible erosion resistant blanket that allows for rapid germination and accelerated plant growth.

## Recommended Applications

- Erosion control and revegetation for moderate slopes ( $\leq 2H:1V$ )
- Rough graded slopes
- Enhancement of vegetation establishment

## Technical Data

Physical Properties*	Test Method	Units	Tested Value
Specification for Hydraulically-Applied Wood Fiber Mulch	ASTM D8198-Type1	Compliant	Yes
Mass/Unit Area	ASTM D6566 <sup>1</sup>	g/m <sup>2</sup> (oz/yd <sup>2</sup> )	$\geq 336$ (9.9)
Water Holding Capacity	ASTM D7367	%	$\geq 1,200$
Material Color	Observed	n/a	Green
Performance Properties*	Test Method	Units	Tested Value
Cover Factor <sup>2</sup>	ASTM D8298-Type 1	n/a	$\leq 0.25$
Percent Effectiveness <sup>3</sup>	ASTM D8298-Type 1	%	$\geq 75$
Vegetation Establishment	ASTM D7322	%	$\geq 250$
Functional Longevity <sup>4</sup>	ASTM D5338	months	$\leq 3$
Environmental Properties*	Test Method	Units	Tested Value
Ecotoxicity <sup>5</sup>	EPA 2021.0	n/a	Non-Toxic
Biodegradability	ASTM D5338	n/a	Yes
USDA BioPreferred® Biobased Content	ASTM D6866	%	99
Elemental Impurity Limits	ASTM D8082	Pass/Fail	Pass
Carbon Footprint <sup>6</sup>	Life Cycle Assessment	Unit CO <sub>2</sub> e/Unit of product <sup>7</sup>	$\leq 0.4$



Product Composition	Typical Value
Thermally Processed Wood Fibers <sup>8</sup> (within a pressurized vessel)	97%
Wetting Agent-Including high-viscosity colloidal polysaccharides	3%

\* When uniformly applied at a rate of 3,000 pounds per acre (3,400 kilograms/hectare) under laboratory conditions. 1. ASTM test methods developed for Rolled Erosion Control Products that have been modified to accommodate Hydraulic Erosion Control Products. 2. Cover Factor is calculated as soil loss ratio of treated surface versus an untreated control surface. 3. % Effectiveness = One minus Cover Factor multiplied by 100%. 4. Functional Longevity is the estimated time period, based upon field observations, that a material can be anticipated to provide erosion control and agronomic benefits as influenced by composition, as well as site-specific conditions, including; but not limited to – temperature, moisture, light conditions, soils, biological activity, vegetative establishment and other environmental factors. 5. 48-hour LC<sub>50</sub> > 100% - LC<sub>50</sub> refers to the percent concentration of a substance in water when 50% percent mortality of an organism is reached. 50% mortality of the tested species (*Daphnia magna*) could not be achieved when subjected to 100% effluent concentration proving the material to be acutely non-toxic. 6. Cradle to factory gate (Conover, NC) life cycle assessment. 7. "Carbon dioxide equivalent" or CO<sub>2</sub>e is a term for describing different greenhouse gases in a common unit. For any quantity and type of greenhouse gas, CO<sub>2</sub>e signifies the amount of CO<sub>2</sub> which would have the equivalent global warming impact. The unit of CO<sub>2</sub>e per unit of product is a consistent ratio based on mass, regardless of what unit of mass is chosen. For instance, there is 0.4 kg of CO<sub>2</sub>e per kg of product or 0.4 oz CO<sub>2</sub>e per oz of product. 8. Heated to a temperature greater than 380 degrees Fahrenheit (193 degrees Celsius) for 5 minutes at a pressure greater than 50 psi (345 kPa) in order to be Thermally Refined™/Processed and to achieve phytosanitation.



## Packaging Data

Properties	Test Method	Units	Nominal Value
Bag Weight	Scale	kg (lb)	22.7 (50)
Bags per Pallet	Observed	#	40

UV and weather-resistant plastic bags. Pallets are weather-proof stretch wrapped with UV resistant pallet cover.

## Profile Products

750 Lake Cook Road, Ste. 440  
Buffalo Grove, IL 60089  
800-508-8681 or +1-847-215-3464  
[www.profileproducts.com](http://www.profileproducts.com)

To the best of our knowledge, the information contained herein is accurate. However, Profile Products cannot assume any liability whatsoever for the accuracy or completeness thereof. Final determination of the suitability of any information or material for the use contemplated, of its manner of use and whether the suggested use infringes any patents is the sole responsibility of the user.  
Profile Products 2022©