

MATERIAL PROPERTY DATA SHEET



F80-X-Z SERIES

PATENT PENDING

Specifications

Falcon Percussion Driven Anchors (PDAs) are designed to provide drive efficiency and maximize load capability across a wide range of applications. The F80-X-Z assembly consists of a top plate that allows for vegetation establishment with one-way wire grip, tethered to a deep-seated earth anchor. Once the anchor is driven into the ground, typically 3 feet (0.9 m), the top plate is secured to the ground and held fast, holding an HPTRM or structure firmly in place. The anchor and top plate of the F80-X-Z are cast in the USA. The assembly is fabricated in the USA. The F80-X-Z assembly allows for re-tensioning, negates the need for time consuming cable crimping and comes fully assembled.



Typical Pullout Resistance*		
Soil Type	Install Depth	
	3 ft	5 ft
Loose (SPT > 4)	150	250
Medium (SPT > 10)	450	650
Dense (SPT > 30)	1,100	2,000
Very Dense (SPT > 50)	2,000	4,000

System Performance	
Typical Anchor Load*	750 lbs
Maximum Working Load	1,300 lbs
Ultimate Assembly Strength	1,500 lbs
Ultimate Cable Strength	2,100 lbs

Assembly Components†		Physical Properties
Top Plate	Zinc-aluminum alloy	Diameter: 4.0" (100 mm) Thickness: 0.11" (2.8 mm) Open Area: 50%
Grip	Spring-loaded crush roller	Ceramic
Cable	Zinc-aluminum coated steel	Diameter: 1/8" (3.1 mm)
Anchor	Zinc-aluminum alloy	3.1 L x 1.3 W x 1.1 H inches (80 L x 33 W x 28 H mm) Bearing Area: 3.4 in ² (22 cm ²)
Length	Varies	F80-X-Z3: 3 ft (0.9 m) F80-X-Z6: 6 ft (1.8 m) Additional Lengths Available

Typical Use
Upgraded strength, light duty assembly - used for standard ARVS systems

* Soil dependent value.

† Assembly is shown as standard configuration. Cable lengths and other components may be customized as required.

Disclaimer: The information contained herein may represent product index data, performance ratings, bench scale testing or other material utility quantifications. Each representation may have unique utility and limitations. Every effort has been made to ensure accuracy; however, no warranty is claimed and no liability shall be assumed by Western Green or its affiliates regarding the completeness, accuracy or fitness of these values for any particular application or interpretation. While testing methods are provided for reference, values shown may be derived from interpolation or adjustment to be representative of intended use. For further information, please feel free to contact Western Green.

©2021, Falcon Anchors is a registered trademark from Western Green. Certain products and/or applications described or illustrated herein are protected under one or more U.S. patents. Other U.S. patents are pending, and certain foreign patents and patent applications may also exist. Trademark rights also apply as indicated herein. Final determination of the suitability of any information or material for the use contemplated, and its manner of use, is the sole responsibility of the user. Printed in the U.S.A.





Bowman
Construction
Supply Inc.



Quick
Supply Co.



Cascade
GEOSYNTHETICS

LOCATIONS & CONTACT INFO

ASP ENTERPRISES

aspent.com
salesasp@aspent.com

BOWMAN CONSTRUCTION SUPPLY

bowmanconstructionsupply.com
salesbcs@bowmanconstructionsupply.com

QUICK SUPPLY CO.

quicksupplyco.com
salesquick@quicksupplyco.com

CASCADE GEOSYNTHETICS

cascadegeos.com
salescascade@cascadegeos.com

St. Louis, MO 636.343.4357
Omaha, NE 402.861.8579
Kansas City, MO 816.554.1191
Wichita, KS 316.393.1554

Denver, CO 303.696.8960
Colorado Springs, CO 719.257.7840
Loveland, CO 970.535.0863

Des Moines, IA
515.289.1271

Portland, OR
971.339.1020

SOLUTIONS WE SUPPLY

GEOSYNTHETICS

Filter Fabrics

Stabilization Fabrics

Geogrids

- Road Grids
- Wall Grids
- Slope Stabilization

Specialty Fabrics

Composite Geomembranes

- GCLs, PVC, HDPE, LLDPE, EPDM, Granular Bentonite

SEDIMENT CONTROL

Inlet Protection

- Grated Inlet, Curb Inlet, Area Inlet Protection

Ditch Checks

- Triangle Silt Dike
- GeoRidge

Perimeter Protection

- High and Low-Porosity Silt Fence, Straw Wattles, Silt Socks
- Safety Fence

Flocculants & Water Treatment

- Polymer-Based & Natural Flocculants

Sediment Basin Skimmers

Dewatering Bags

Trackout Control

- FODS
- Rumble Grates

Turbidity Curtains

EROSION CONTROL

Basic Hydraulically Applied Mulches

- Wood
- Paper
- Blends
- Straw

High-Performance Hydraulically

Applied Products

- BFM
- FGM
- Additives & Tackifiers

Temporary Erosion Control Blankets

- Coir & Jute Mat/Nettings
- Short-Term ECBs
- Extended-Term ECBs

Permanent Erosion Control Blankets

- Turf Reinforcement Mats
- HP-TRMs
- Anchor Reinforced Vegetation System

Structural BMPs

- Transition Mats
- Geoweb Cellular Confinement
- Composite Vegetated Armor System
- Flex MSE Vegetated Wall System
- Articulated Concrete Block
- Gabions
- Grout-Filled Geotextile Mats

Vegetation Establishment

- Native Seed & Turf Seed
- Fertilizers
- Organic Soil Additives
- Stratavault Soil Cells

STORMWATER MANAGEMENT

Water Quality

- Inlet Filter Boxes
- Pre-Treatment Chamber
- Nutrient Separating Baffle Boxes
- High-Flow Biofiltration Media
- Hydrodynamic Separators
- Stratavault

Water Quantity

- Modular Underground Storage Systems
- Chamber Detention Systems

Drainage

- HDPE Swale Liner
- Pipe & Fittings
- Drainage Composites
- Strip Drain

Inlet Structures

- PVC
- Drain Basins, In-Line Drains
- Landscape

Permeable Pavers

- Permeable Articulating Concrete Block
- Grass Pavers
- Gravel Pavers
- Concrete Pavers

SPECIALTY

Natural & Synthetic Coir Fiber Logs

Vegetated Reinforced Soil Slopes

Soil Anchors

Root Barrier System

AquaBlok

Muscle Wall

We are full line distributors of construction materials for all project types. Contact us for assistance with a project. From specification and development to installation and completion, we're here to help with all of your site solution needs.

GEOSYNTHETICS | EROSION CONTROL | STORMWATER MANAGEMENT
SEDIMENT CONTROL | REVEGETATION & SOIL AMENDMENTS